

DESTINATION DISPLAY ULTIMA NSI

ON-BOARD PASSENGER INFORMATION SYSTEM



FEATURES

- Ideal for tour buses
- Energy-efficient LED technology
- Excellent readability



SMALL SIZE, GREAT PERFORMANCE

Ultima NSI can do everything that Luminator's large LED destination displays can do – and in the tightest spaces. Highly efficient SMD LEDs ensure a high light output and excellent readability at a low power consumption. That saves fuel and lowers operating costs.

The focus of the Ultima NSI Destination Sign is on achieving the smallest possible size with a simple installation. That's why the display doesn't have an internal control unit. It connects to the control unit on the bus and is operated from there.

If you're looking for a small display in addition to your large one or if you only have limited space: our smallest display makes up for what it lacks in size with its efficiency and functionality.

DESTINATION DISPLAY ULTIMA NSI

ON-BOARD PASSENGER INFORMATION SYSTEM

TECHNICAL DATA

Order Information	
LTG Switzerland GmbH	imotion LED.mini
Germa (Rastatt)	FUTURA iLED
LTG Sweden AB	MobiSTOP Ultima
Display	
Technology	SMD-LED
Brightness	2000 cd/m2 (max)
Viewing Angle	120° (h), 120° (v)
Software	
Applications	Depending on the system-setups compatible with following Luminator-applications: Backoffice Solutions icenter & MAW Editing Tools TEDplus, MIE & AlphaNT
Update	Via Backoffice Software or RS485 Service Tool
Electrical Properties	
Operating Voltage	12 VDC or 24 VDC (9 - 36 VDC)
Interfaces	
Ethernet	1 x (optional)
RS485	1 x
IBIS-Slave (VDV 300)	1 x
Environment	
Operating Temperature	-40 °C to +70°C
Standards	
ECE-R10 (x)	Compliant
ECE-R118 (x)	Compliant
VDV-300	Compliant

Disclaimer

Features and specifications are subject to change without notice. Properties relating to the Goods contained in this document do not constitute the product specifications but typical values for purposes of description only. February 2023