

ROADRUNNER™ AHD CAMERA, EXTERIOR TAPERED DOME

ON-BOARD VIDEO SECURITY SYSTEM



FEATURES

- Full HD (1080p) Resolution
- 2.9mm Lens
- Vandal and Impact Resistant
- IP66 Rated

RUGGED AND RELIABLE

Providing the highest quality recording in a rugged and vandal resistant enclosure, the exterior tapered dome camera is designed for optimal viewing and flexibility for exterior locations.

UV COATED DOME

The exterior tapered dome camera features a UV coated dome for additional exterior protection.

ROADRUNNER™ AHD CAMERA, EXTERIOR TAPERED DOME

2

TECHNICAL DATA

Order Information	
Order Number North America	RR-CT36-AHD
Electrical Properties	
Operating Voltage	12 VDC
Power Consumption	2.0 W
Current Consumption	170 mA
Interfaces	
12 VDC Input	1, 2-pin Minifit Jr
Video Output	1, BNC Socket (Yellow)
Mechanical Properties	
Weight	0.39 kg, 0.85 lbs
Dimensions	94 mm x 63 mm x 130 mm, 3.7" x 2.48" x 5.12"
Housing Screws	Security Torx
Environment	
Operating Temperature	-10°C to 50°C, 14°F to 122°F
Relative Humidity	0% to 96% (Non-condensing)
Ingress Protection	IP66
Standards	
NDA	✓
FCC	✓
CE	✓

Features and specifications are subject to change without notice.

ROADRUNNER™ AHD CAMERA, EXTERIOR TAPERED DOME

TECHNICAL DATA

Image	
Image Sensor	1/2.9" 2.1M Sony CMOS
Field of View	Horizontal 80°; Vertical 60°
Resolution	F-HD (1920x1080), HD (1280x720), D1 (704x480), n-HD (640x360), CIF (352x240)
Frame Rate	1920x1080p @ 30 fps
Scanning System	Progressive
Shutter Speed	Automatic, 1/30, 1/60, Flicker-less Mode (FLK) ~ 1/50,000 Sec
Pan / Tilt / Zoom	Digital
Light Sensitivity Black/White	0.1 Lux
Light Sensitivity Color	1.0 Lux
Noise Reduction	Dynamic, 3D
Signal-To-Noise Ratio	50dB or Higher
Image Settings	Color, Brightness, Sharpness, Auto Gamma Control, Defog, White Balance
Video	
Video Output Signal	AHD, CVBS
Mechanics	
Lens	3.6 mm